

2022 Mains Power Supply

The BARRETT 2022 is a 13.8V DC regulated, 21 Amp power supply capable of operating on AC input voltages from 88VAC to 264VAC without input voltage switching and is designed to power the Barrett 2000 series of HF transceivers and accessories.

The 2022 has connectors to provide power for one 2000 series transceiver plus one 2000 series accessory such as a modem.

The 2022 has a battery standby system comprising a charging circuit with a true automatic no-break changeover, in case of mains power supply failure. This feature eliminates the problems of data modems re-setting during mains failures and requiring re-initialisation. When mains is present the power supply charges the battery at a maximum rate of 3 amps. When the battery is fully charged the rate is reduced to a trickle charge to prevent over charging.

The 2022 power supply incorporates loudspeakers for the 2000 series transceiver when used in a base station configuration. The loudspeaker is automatically connected to the transceiver via the power connector. The power supply is provided with an internal fan allowing operation at a 100% duty cycle for data applications.

The 2022 power supply is supplied with four IEC cord sets that will suit most mains power outlets used throughout the world.

Specifications

Equipment	BARRETT 2022 mains power supply with no break battery backup charge controller and base station loudspeaker.
Output voltage	13.8V DC
Output current	21 Amps continuous
Input voltage	88 -264 VAC @ 50/60 Hz. Auto-ranging.
Regulation	Less than 1% change at full load
Ripple and noise	Less than 150 mV RMS at full load
Overload protection	105%-135% hiccup mode, auto recovery
Operating temperature	-10°C to +50°C
EMC standards	EN55022 class B, EN 61000-3-2,3 EN61000-4-2,2,3,4,5,6,7,8,11 EN50204
Charger output	13.6 VDC, 3 Amps maximum
Controls	Mains on/off switch, LED condition displays.
Speaker impedance	8 ohm
Speaker power	5 Watts
Connectors DC	2 x DB 15 - 7W2 female for connection to Barrett 2000 series transceivers and accessories. 1 x DB 15 - 7W2 male for connection to auxiliary battery
Connectors AC	IEC
Mounting	Standard bench mounting or optional 19" rack mounting kit (P/N BCA20007)


2022 Mains Power Supply



2022 Power Supply (front panel)



2022 Power Supply (top view)



2022 Power Supply (side view)





2022 Solar Power Supplies

Solar power supplies vary in price based on user requirements. The six solar power supply packages below have very high specifications in terms of allowance for variations in available sun light and have safety margins ranging from 14% to 28%. and array load ratios of 1.5 which is best industry practice for telecommunications solar power supply systems. These systems will operate to specification in Africa, South East Asia, The South Pacific and the Middle East.

Solar packages are quoted without batteries to allow customers to purchase batteries locally as the cost of air-freighting due to battery weights is high. Air-freightable batteries are available if customers prefer a complete package.

Custom solar supplies can be designed and supplied to meet customers exact requirements for different system configurations.

BC202201 ground mounted light duty solar supply
BC202202 roof mounted light duty solar supply

Light duty supplies will power a Barrett 900 or 2000 series transceiver based on a 12 hour operational day (equipment off over night) 2 hours of voice or selcall transmission per 12 hour period and in receive mode for 12 hours.

- Includes:-
- 2 x 75Ahr Solar panels
 - Mounting frame
 - 20A Solar regulator (includes low voltage load cutout)
 - 6m cable from panels to solar regulator
 - 1.5m cable from solar regulator to battery.
 - Bird spikes

BC202203 ground mounted heavy duty solar supply
BC202204 roof mounted heavy duty solar supply

Heavy duty supplies will power a Barrett 900 or 2000 series transceiver based on 4 hours of voice or selcall transmission per 24 hour period and in receive mode for 24 hours.

- Includes:-
- 2 x 110W Solar panels
 - Mounting frame
 - 45A Solar regulator (includes low voltage load cutout)
 - 5m cabling from panels to solar regulator
 - 1.5m cable from solar regulator to battery/batteries.
 - Bird spikes

BC202205 ground mounted heavy duty solar supply
BC202206 roof mounted heavy duty solar supply

Data system solar power supplies will power a Barrett 900 or 2000 series transceiver, with data modem and notebook computer, based on 6 hours of data, voice or selcall transmission per 24 hour period and in receive mode for 24 hours.

- Includes:-
- 11 x 125W Solar panels
 - Mounting frame
 - 2 x 60A Solar regulator (includes low voltage load cutout)
 - 5m cable from panels to solar regulators
 - 2m cable from solar regulator to batteries.
 - Bird spikes

Accessories

- BCA92203** 100 AH 12V sealed solar block battery - air-freightable
- BCA92208** Cabling kit for paralleling batteries - per additional battery, consists of two heavy duty cables with lugs and two battery lugs



2022 Solar Power Supplies

Head Office:

Barrett Communications Pty Ltd P O Box 1214, Bibra Lake WA 6965 AUSTRALIA
Toll Free Tel: 1800 999 580 Tel: (618) 9434 1700 Fax: (618) 9418 6757
email: information@barrettcommunications.com.au

European Office:



01030 Украина Киев а/я 186

КОНЦЕРН АЛЕКС

ЦЕНТРАЛЬНЫЙ ОФИС В КИЕВЕ
+380 (44) 246-46-46
+380 (44) 246-47-00
mail@alex-ua.com
www.alex-ua.com



MADE IN AUSTRALIA



No 149438

